




Sanitary  
flow  
equipment



## 7RMP-TC REDUCING TEE Clamp Dimensions



Dimensions and tolerance according to ASTM A270 - ASTM A269, compliant with ASME BPE table # DT-19

Ordering code	Size inch	A inch - mm	B inch - mm	C inch - mm
7RMP-A075X050--	3/4" x 1/2"	2.500 - 63,5	2.500 - 63,5	5.00 - 127,0
7RMP-A100X050--	1" x 1/2"	2.625 - 66,7	2.625 - 66,7	5.25 - 133,4
7RMP-A100X075--	1" x 3/4"	2.625 - 66,7	2.625 - 66,7	5.25 - 133,4
7RMP-A150X050--	1 1/2" x 1/2"	2.875 - 73,0	2.875 - 73,0	5.75 - 146,0
7RMP-A150X075--	1 1/2" x 3/4"	2.875 - 73,0	2.875 - 73,0	5.75 - 146,0
7RMP-A150X100--	1 1/2" x 1"	2.875 - 73,0	2.875 - 73,0	5.75 - 146,0
7RMP-A200X050--	2" x 1/2"	3.375 - 85,7	3.125 - 79,4	6.75 - 171,4
7RMP-A200X075--	2" x 3/4"	3.375 - 85,7	3.125 - 79,4	6.75 - 171,4
7RMP-A200X100--	2" x 1"	3.375 - 85,7	3.125 - 79,4	6.75 - 171,4
7RMP-A200X150--	2" x 1 1/2"	3.375 - 85,7	3.125 - 79,4	6.75 - 171,4
7RMP-A250X050--	2 1/2" x 1/2"	3.625 - 92,1	3.375 - 85,7	7.25 - 184,2
7RMP-A250X075--	2 1/2" x 3/4"	3.625 - 92,1	3.375 - 85,7	7.25 - 184,2
7RMP-A250X100--	2 1/2" x 1"	3.625 - 92,1	3.375 - 85,7	7.25 - 184,2
7RMP-A250X150--	2 1/2" x 1 1/2"	3.625 - 92,1	3.375 - 85,7	7.25 - 184,2
7RMP-A250X200--	2 1/2" x 2"	3.625 - 92,1	3.375 - 85,7	7.25 - 184,2
7RMP-A300X050--	3" x 1/2"	3.875 - 98,4	3.625 - 92,1	7.75 - 196,8
7RMP-A300X075--	3" x 3/4"	3.875 - 98,4	3.625 - 92,1	7.75 - 196,8
7RMP-A300X100--	3" x 1"	3.875 - 98,4	3.625 - 92,1	7.75 - 196,8
7RMP-A300X150--	3" x 1 1/2"	3.875 - 98,4	3.625 - 92,1	7.75 - 196,8
7RMP-A300X200--	3" x 2"	3.875 - 98,4	3.875 - 98,4	7.75 - 196,8
7RMP-A300X250--	3" x 2 1/2"	3.875 - 98,4	3.875 - 98,4	7.75 - 196,8
7RMP-A400X050--	4" x 1/2"	4.750 - 120,7	4.125 - 104,8	9.50 - 241,4
7RMP-A400X075--	4" x 3/4"	4.750 - 120,7	4.125 - 104,8	9.50 - 241,4
7RMP-A400X100--	4" x 1"	4.750 - 120,7	4.125 - 104,8	9.50 - 241,4
7RMP-A400X150--	4" x 1 1/2"	4.750 - 120,7	4.125 - 104,8	9.50 - 241,4
7RMP-A400X200--	4" x 2"	4.750 - 120,7	4.375 - 111,1	9.50 - 241,4
7RMP-A400X250--	4" x 2 1/2"	4.750 - 120,7	4.375 - 111,1	9.50 - 241,4
7RMP-A400X300--	4" x 3"	4.750 - 120,7	4.375 - 111,1	9.50 - 241,4

### Material :

ASTM A 479 / ASTM A 182 - 316L (wn. 1.4404 - 1.4435)

### Dimensions & Tolerances :

Dimensions as specified in ASME-BPE Part DT

**General Note** Tolerance end-to-end, center-to-end : dimension **C** is 0.050 inch (=1,27 mm). All dimensional characteristics are inspected 100% for tolerances listed in Table DT-5 in the ASME-BPE specifications.

### Surface finish :

Internal standard surface finish comply with ASME BPE Part SF Table # SF-4 surface designation code SFF2 with Ra average 0,5 micron or better, mechanically polished. External surface scotch brite

### Marking:

Each 7RMP- reducing tee clamp are marked with material designation e.g. 316L SS  
3A and Heat No. for full lot traceability according to Aerrex Innox QA routines.

**Get the information you need and more at : [info@aerreinox.it](mailto:info@aerreinox.it)**

In the interests of development and improvement of the product, we reserve the right to change the specifications without prior notice.

**Aerrex Innox s.r.l.**

26010 FIESCO Via Gerola n.4 -CREMONA- Italy  
Tel. +39.0374.370828 Fax +39.0374.370833  
e-mail : [info@aerreinox.it](mailto:info@aerreinox.it) http : [www.aerreinox.it](http://www.aerreinox.it)